




九、引下夹具 Nine, lead the fixture




橡胶型杆用引下夹具
Rubber type rod for lowering fixture



金属型杆用引下夹具
Metal type rod for lowering fixture



橡胶型塔用引下夹具
Rubber type tower lowering fixture



金属型塔用引下夹具
Metal type tower lowering fixture

用途、材料：Usage, material:

引下夹具用于光缆引下及跳接时固定光缆，每1.5-2.0米光缆需安装一套。

并沟线夹——耐老化橡胶或铝合金 不锈钢带抱箍——不锈钢 支座——铝合金 U型钢——镀锌钢

The lower clamp is used to fix the optical cable when the cable is led down and jumped, and one set is required for each 1.5-2.0 m cable.
groove clamp – anti-aging rubber or aluminum alloy stainless steel belt hoop – stainless steel bearing – aluminum alloy U-shaped steel – galvanized steel

表9.1规格 Table 9.1 Specifications

产品名称Product Name	型号 Model	适用缆径(mm) Applicable Cable Diameter (mm)	重量(kg) Weight (kg)	备注 Remarks
橡胶型塔用引下夹具	TGY 1110-T	9.00-11.1	0.85	用于ADSS光缆
	TGY 1330-T	11.2-13.3	0.85	用于ADSS光缆
	TGY 1550-T	13.4-15.5	0.85	用于ADSS光缆
	TGY 1800-T	15.6-18.0	0.85	用于ADSS光缆
金属型塔用引下夹具	TGY 240-T	8.50-24.0	0.85	用于OPGW光缆
橡胶型杆用引下夹具	TGY 1110-H*	9.00-11.1	0.95	用于ADSS光缆
	TGY 1330-H*	11.2-13.3	0.95	用于ADSS光缆
	TGY 1550-H*	13.4-15.5	0.95	用于ADSS光缆
	TGY 1800-H*	15.6-18.0	0.95	用于ADSS光缆
金属型杆用引下夹具	TGY 240-H*	8.50-24.0	0.95	用于OPGW光缆

注：杆用引下夹具中 H * 表示不锈钢带抱箍，型号按表9.2确定。

Note: In the rod lowering fixture, H * means stainless steel belt hoop, the model is determined according to Table 9.2.