

导线接续管补强接续条 Reinforced Conductor Splice

导线接续管补强接续条是用来加强接续并且使接续强度超过导线的RBS。
Reinforced Conductor Splice is used to reinforce the splice and make its splice intensity more than the conductor's RBS.

表6-5导线接续管补强接续条选型表 Model table

产品型号 Product model	适用导线直径范围 Cable range(mm)		适用导线类型 Suitable conductor type(GB1179-83)			接续管最大长度 Ref clamp length (mm)	参考线夹长度 Reference length (mm)	线夹重量 Weight (kg)	
	最小Min.	最大Max.	钢芯铝绞线LGJ/LGJF ACSR	接续管类型 splicing sleeve type	铝绞线LJ Aluminum strand conductor				接续管类型 splicing sleeve type
BJL-131	12.24	12.78			95	JT-95L	280	1470	0.5
BJL-133	13.26	13.82	95/15	JT			690	2010	0.9
BJL-134	13.83	14.4	95/20	JT	120	JT-120L	690	2040	0.9
BJL-135	14.41	15.09	120/20	JY/JTB			430	2000	1.1
BJL-137	15.72	16.36	120/25	JY	150	JT/JY-150L	490	2060	1.2
BJL-138	16.37	17.04	150/20	JY/JTB			470	2250	1.5
BJL-139	17.05	17.78	150/25、150/35	JY/JTB	185	JT/JY-185L	530	2220	1.5
BJL-141	18.53	19.3	185/25、185/30	JY/JTB	210	JY-210L	540	2510	2.3
BJL-142	19.31	20.12	185/45、210/25	JY/JTB	240	JY-240L	570	2550	2.6
BJL-143	20.13	20.96	210/35、210/50	JY/JTB			600	2760	2.8
BJL-144	20.97	21.61	240/30	JY/JTB			570	2830	2.7
BJL-145	21.62	22.5	240/40、240/55	JY/JTB	300	JY-300L	640	3090	3.4
BJL-146	22.51	23.6	300/15、300/20	JY/JYD			580	3180	4.5
BJL-147	23.61	24.59	300/25、300/40、300/50	JY/JYD			660	3410	5.2
BJL-148	24.6	25.6	300/70	JY/JYD			720	3570	5.6
BJL-149	25.61	26.67	400/25	JY/JYD	400	JY-400L	660	3770	5.9
BJL-150	26.68	27.71	400/35、400/50	JY/JYD			730	4000	6.7
BJL-151	27.72	28.87	400/65	JY/JYD			760	4280	9.2
BJL-152	28.88	30.05	400/95、500/35、500/45	JY/JYD	500	JY-500L	830	4450	9.7

注:本表只列出部分产品。 Note: this table is simply listed some products.

表6-6导线接续管补强接续条选型表(适用于500kV线路) Model table (500kV)

产品型号 Product model	适用导线直径范围 Cable range(mm)		适用导线类型 Suitable conductor type(GB1179—83)				接续管最大长度 Ref clamp length (mm)	参考线夹长度 Reference length (mm)	线夹重量 Weight (kg)
	最小Min.	最大Max.	钢芯铝绞线LGJ/LGJF ACSR	接续管类型 splicing sleeve type	铝绞线LJ Aluminum strand conductor	接续管类型 splicing sleeve type			
BJL—146	22.51	23.60	300/15、300/20	JY/JYD			580	3180	4.5
BJL—147	23.61	24.59	300/25、300/40、300/50	JY/JYD			660	3410	5.2
BJL—148	24.60	25.60	300/70	JY/JYD			720	3570	5.6
BJL—149	25.61	26.67	400/25	JY/JYD	400	JY—400L	660	3770	5.9
BJL—150	26.68	27.71	400/35、400/50	JY/JYD			730	4000	6.7
BJL—151	27.72	28.87	400/65	JY/JYD			760	4280	9.2
BJL—152	28.88	30.05	400/95、500/35、500/45	JY/JYD	500	JY—500L	830	4460	9.7